


Series 3500 In-Line Externally Pressurized Pressure Balanced Expansion Joints

Series 3500 In-Line Pressure balanced expansion joints provide the same benefits as the standard design with the added advantage of internally reacting the pressure thrust by linking an additional bellows designed with twice the effective area of the expansion bellows. The design eliminates the requirement for main anchors to react the pressure thrust—only intermediate anchors must be provided to restrain the bellows spring force. Technical data is provided in Tables 9 and 10 for sizes 4" through 24".

3501PB Fixed Flange



3502PB Weld End




Table 9 Type 3501PB & 3502PB

Design Pressure: 150 psig Test Pressure: 225 psig Design Temperature: 500°F

Nominal Size (NPS)	Axial Spring Rate (1) (lb/in)	Part Number 3501PB 3502PB	Axial Compr. (inches)	Axial Ext. (inches)	3501PB		3502PB	
					Overall Length (inches)	Weight (lbs)	Overall Length (inches)	Weight (lbs)
4	638	-148-4	4	1	41.0	218	39.0	196
	408	-148-6	6	2	57.0	296	55.0	274
	320	-148-8	8	2	68.0	349	66.0	328
5	885	-155-4	4	1	41.0	278	39.0	255
	576	-155-6	6	2	57.0	264	55.0	339
	473	-155-8	8	2	68.0	441	66.0	417
6	1056	-160-4	4	1	43.0	336	39.0	302
	688	-160-6	6	2	59.0	436	55.0	400
	569	-160-8	8	2	70.0	528	66.0	492
8	1577	-167-4	4	1	43.0	488	39.0	437
	1014	-167-6	6	2	59.0	656	55.0	605
	786	-167-8	8	2	70.0	766	66.0	715
10	1930	-174-4	4	1	43.0	587	40.0	521
	1241	-174-6	6	2	59.0	776	56.0	720
	965	-174-8	8	2	70.0	916	67.0	850
12	2822	-180-4	4	1	48.0	798	42.0	705
	1796	-180-6	6	2	64.0	1055	57.0	962
	1518	-180-8	8	2	75.0	1212	69.0	1109
14	4726	-181-4	4	1	48.0	939	42.0	794
	3038	-181-6	6	2	64.0	1197	57.0	1053
	2363	-181-8	8	2	75.0	1405	69.0	1260
16	5116	-182-4	4	1	48.0	1097	42.0	922
	3289	-182-6	6	2	64.0	1386	57.0	1221
	2558	-182-8	8	2	75.0	1613	69.0	1438
18	5766	-183-4	4	1	49.0	1191	42.0	1013
	3706	-183-6	6	2	64.0	1518	57.0	1341
	2882	-183-8	8	2	76.0	1771	69.0	1597
20	5040	-184-4	4	1	49.0	1340	42.0	1130
	3241	-184-6	6	2	64.0	1699	57.0	1489
	2520	-184-8	8	2	76.0	1978	69.0	1768
24	5674	-186-4	4	1	50.0	1559	42.0	1285
	3648	-186-6	6	2	65.0	1980	57.0	1706
	2837	-186-8	8	2	77.0	2306	69.0	1928
1	2	3	4	5	6	7	8	9